

High Pressure Single Station Rotary Spray Washer For Aircraft Engine Gearbox



Bakr single station rotary spray cleaner adopt the principle of high-pressure water jet-flowing, combined with rotary tooling basket, adopts PLC touching screen controlling, highly automatic available. The lid can be automatic opening and closing ,360° all directions cleaning , whole cleaning process can be automatic completed . Regarding to the product design, comprehensive consideration of practicality, ergonomics, aesthetics and other aspects, according to the accumulation of long-term experience and real operation, we have developed a set of standardized models.

Heating Power	8KW
Accessories	Lid , Inlet , Valve , Drain Valve
Function	Basket Rotary, Or Spray Pipeline Rotary
Voltage/Power Supply	220V/380V/415V/440V Optional
Material	Stainless Steel 304
Applications	Carbon Clean, Oil, Grease, fouls clean, Cutting Liquids, Metal Particles, Dirties Clean
Timer/Temperature	Digital
Loading Weight(Kg)	100
Liquid Storage Tank Capacity Clean/Rinsing	240L
Advantages	High Efficiency, high reliability, No Damage to cleaning parts, Cleaning Completely, environment protective
Optional Function	Rinsing, Air Cut, Vapor demist and condensing drying, Loading trolley, Oil skimmer, Auto water filling

PRODUCT DISPLAY

MANUAL



AUTO



Basic functions

PLC & Touch screen auto control, rotary disk or spray pipeline for parts all-dimensional spray cleaning, ultrasonic cross cleaning, quick fluid exchange, high efficiency oil-water separation, cleaning fluids extractive filtration system, thus to be provided with the optional functions as clean, rinsing, air cut, drying, high precision cleaning and advanced demist system.

CLEANING PARTS GALLERY



ALL SPECIFICATIONS

Cleaning Process	Model	Overall Dimensions When Closed L*W*H (cm)	Washing Capacity Φ *H(cm)	Load Capacity (Kg)	Liquid Storage Tank Capacity Clean/Rinsing (L)	Washing Pump Spray Pressure (Clean/Rinsing) (Bar)	Heating Power (Clean/Rinsing) (KW)
Single Spray Cleaning	BK-100 OAP	203*258*200	Φ 90*70	600	450	5,07,5	12,0
	BK-120 OAP	226*298*210	Φ 110*80	600	550	5,07,5	18,0
	BK-140 OAP	246*330*220	Φ 128*90	600	750	5,07,5	24,0
	BK-180 OAP	279*396*232	Φ 165*100	800	1000	5,07,5	30,0
	BK-220 OAP	326*480*236	Φ 200*100	800	1200	5,07,5	40,0
Spray Cleaning +Rinsing	BK-100 OBP	242*258*200	Φ 90*70	600	300/300	5,0[7,5]/2,5	12,0/12,0
	BK-120 OBP	265*298*210	Φ 110*80	600	400/400	5,0[7,5]/2,5	12,0/12,0
	BK-140 OBP	285*330*220	Φ 128*90	600	500/500	5,0[7,5]/2,5	18,0/18,0
	BK-180 OBP	318*396*232	Φ 165*100	800	700/700	5,0[7,5]/2,5	24,0/24,0
	BK-220 OBP	365*480*236	Φ 200*100	1000	800/800	5,0[7,5]/2,5	30,0/30,0