




Climate Chamber with Humidity Control Plant Growth Chamber

◎ Light culture of microorganism, cell tissue, seedling, insect and small animal under the control of precise humidity.

Characteristics:

- Double door structure, with high quality stalinite to observe sample.
- 7.0 inch true color touch screen display, convenient to view historical temperature data and appointment auto start and stop.
- Full spectrum Multi-stage adjustable, 30 sections programmed Temp. LUX ,RH controller.
- Full spectrum LED top light source design, high illumination, low thermal radiation, long service life, removable Light partition, adjustable layer space.
- Internal humidification system. Small humidifier particles, high humidity uniformity, small water consumption, with automatic water intake, water shortage alarm function.
- The evaporator temperature is collectively controlled by the backflow valve and expansion valve, greatly prolonging the service life of the compressor.
- Imported high quality temperature sensor and compressor.



Main Technical Parameters:

Patent No. : ZL 2018 3 0095051.6

Model		CC-250	CC-350	CC-450
Cycle Mode		Forced convection, Rear micropore. Supply air in front of the plate		
Function	Temp. Range	Without illumination: 0 ~ 65°C; With illumination: 10 ~ 65°C		
	Temp. Resolution Ratio	0.1°C		
	Temp. Motion	± 0.5°C		
	Temp. Uniformity	± 1.0°C		
	Illumination(LX)	Full spectrum 0-30000LX many degrees for adjusting		
	Humidity Range	40% ~ 95%RH		
Structure	Humidity Motion	± 5% RH		
	Inner Chamber	SUS304 stainless steel sheet		
	Outer Shell	Cold rolling steel electrostatic spraying exterior		
	Thermal Insulation Material	Polyurethane		
	Light barrier	Standard four layer full spectrum LED lamp board		
	Heater	Stainless steel heating tube		
	Power Rating	2.0kw	2.2kw	2.5kw
	Compressor	Air cooled hermetic compressor		
	Coolant	R134A		
	Defrosting Structure	Automatic		
	Humidity control mode	Automatic		
	Leading wire hole	The outer diameter of standard inflation port interface is 10mm		
Controller	Temp. control mode	30 sections program		
	Temp. setting mode	Touch screen settings		
	Temp. display mode	7.0 inch true color touch screen display		
	Operation function	Fixed temperature operation, timing function, auto stop. Appointment start, Program operation		
	Program pattern	Standard configuration		
	Sensor	PT100 Temp. Sensor, Imported chip humidity sensor		
Safety device		Over temperature will automatically cut off the heating, long-term under temperature cut off the refrigeration system, protect the sample; loop self diagnosis		
Specification	Inner Chamber size(W*L*H)(mm)	600*500*840	630*580*960	630*670*1100
	Exterior size (W*L*H)(mm)	794*726*1600	824*806*1720	824*896*1860
	Packing size (W*L*H)(mm)	893*863*1850	943*923*1960	823*1033*2110
	Volume	250L	350L	450L
	Load per rack	15kg		
	Shelf space	120mm		
Accessory	Supply (50/60Hz) Current rating	AC220V/9.1A	AC220V/10A	AC220V/11.5A
	NW/GW (kg)	225/255	260/300	310/350
	Shelf	4		
	Shelf plate	8		
Optional accessories		Light barrier, USB interface and upper computer software, printer, wireless SMS alarm, CO2 concentration control		